

ROTOSEEDER

UNIVERSAL SEEDER

Einböck



Einböck

UNIVERSAL SEEDER

ROTOSEEDER

ROTOSEEDER

SIMPLE AND EFFICIENT TO **MORE SOIL VITALITY**

The ROTOSEEDER is a versatile oversowing tool for dispensing rotational or permanent fallow, intercrops, grass seeds, seeds for simultaneous cropping, slug pellets and similar granules as well as small seeds. The sowing volume is adjustable on the stepless feed valve in a quick and easy way to suit the sowing purpose. The RPM of the scatter disc determines the working width. Through its design, construction and function the ROTOSEEDER offers an extremely cost efficient alternative for the cultivation of fallow areas, intercrops and simultaneous cropping.

Serienausstattung ROTOSEEDER

12 Volt electric drive, charged by a simple connection to the tractor battery

Stepless adjustment of seeding quantity and speed control

Compact and stable construction, easily mountable to a big variety of machines

Scatter disc with adjustable casting shovels and special stirring shaft for grass

Baffle plate for precise adjustment of the working width range and the spreading characteristics

Convenient to operate, user friendly control from the driver cabin

3 m power supply cable from battery to control unit

6 m cable from control unit to seeder

Airtight foil-covered control unit and mounting console for the tractor cabin

Height-adjustable frame with top link mounting and clamping plate

Draining outlet with screwed cover

Hexagonal container guarantees higher container stability as standard types

Screwed cover

Powder coated frame

Operating instructions

Control unit with mounting console for the tractor



Front mounted with upper-linkage mount console



ELECTRONICAL CONTROL UNIT „WORLD“

- stepless rpm setting
- digital rpm indication
- rpm monitoring and measuring guarantee constant rpm and make sure a diminishing seed amount in the tank will not influence the working width
- seed valve indicator (open/closed)
- automatic start-up mechanism for stuck seeds
- area calculator (ha)
- voltage monitor
- temperature indicator
- counter for operating hours
- choice of various languages
- sensor control for automatic opening and closing of the seed valve upon lifting or lowering the machine

Wunschausrüstung ROTOSEEDER

Mounting console for tined weeder

Extension cable 5 meters

Sensor for 3 point linkage

Technische Daten ROTOSEEDER

Type/Electronic control unit	Working width ¹ m	Height/Length/Depth cm	Tank volume litres	Weight approx. kg
ROTOSEEDER WORLD	1 - 20	85/55/60	90	30

¹ depending on seed

Technical data and measurements are approximate and non-binding. We reserve the right to change construction and specification.

Einböck GmbH & CoKG
Schatzdorf 7
A-4751 Dorf / Pram
AUSTRIA

Tel: (+43) 7764 64660
Fax: (+43) 7764 6466-385
www.einboeck.at
info@einboeck.at

Einböck